

7. Pre-treatment

7. Pre-treatment

8. Standard primer coating

primer coating

8. High corrosion resistant

Reverse coating or high durability polyester coating

ISO CATEGORIES

ISO Category E - VERY SEVERE

Characterised by:

- Heavy salt deposits.
- The almost constant smell of salt spray in the air.
- Close to breaking surf (typically 50-200 metres) as found on exposed coasts.

This environment may be extended inland by prevailing winds and local conditions.

ISO Category D - SEVERE

Characterised by:

- Light salt deposits.
- A frequent smell of salt in the air.
- Typically 200-500 metres from breaking surf as found on exposed coasts.
- In the vicinity of large expanses of calm salt water This environment may be extended inland by prevailing winds and local conditions

ISO Category C - MODERATE

COLORBOND® ULTRA™ RECOMMENDED ROOFING AND CLADDING WARRANTY GUIDE

No warranty 0-50m from breaking surf.

10 years: covering the paint surface

against flaking and peeling.

against perforation as a result of 12 years:

corrosion.

covering the paint surface 15 years: against flaking and peeling.

against perforation as a result of

corrosion.

15 years: covering the paint surface

against flaking and peeling.

20 years: against perforation as a result of

corrosion.



ISO CATEGORIES

ISO Category D - SEVERE

Characterised by:

15 years:

- · Light salt deposits.
- · A frequent smell of salt in the air.
- Typically 200-500 metres from breaking surf as found on exposed coasts.
- In the vicinity of large expanses of calm salt water.

This environment may be extended inland by prevailing winds and local conditions.

ISO Category C - MODERATE

Characterised by:

10 years:

- No obvious marine or industrial influences.
- Little or no salt deposits. The occasional smell of salt in the air.
- Typically 500-1000 metres from breaking surf or more than 500 metres from industrial emissions or in the immediate vicinity of calm salt water.

COLORBOND® XRW™ RECOMMENDED ROOFING AND CLADDING WARRANTY GUIDE

10 years: covering the paint surface

against flaking and peeling.

against perforation as a result 10 years:

of corrosion.

covering the paint surface 10 years:

against flaking and peeling.

against perforation as a result

of corrosion.

SEVERE