



RPFL SuperDek® Colorbond® XRW/Ultra
0.42BMT/0.48BMT wall cladding. Base Materials: Steel
Grade G550. BMT 0.42.Mass 4.3kg/m² or 0.48BMT
4.9kg/m². AZ 150 coating for XRW & AZ 200 coating for
Ultra. Profiles tested for Cyclonic Conditions.

Kingspan AIR-CELL INSULINER Self-Supported
3-in-1 Insulation Vapour Barrier and Radiant Barrier
or 430 WF Med. duty sisalation.

Flashguard Soft Edge flashing for metal roof accessories

Top & Bottom Infill Strips/filler block or profiled foam fillers
insert between roof cladding and flashing.

BRA Self Drilling Metal (SDM) screws 14g-10x65 CL4/B8
coating to AS 3566 class 4. Tested & Certified to AS/NZS
1170.2 & BCA 2006 specification B1.2 for the design of building
in cyclone area. For Coldformed Purlins. Fixed at every stud.
And Rivets Aluminum 5052 & Steel Truss Head 4-3 Painted

RPFL Std Colorbond® XRW/Ultra 0.55 BMT Internal Corner Flashing
Base Materials: coating AZ200 Steel Grade G300.
fixed to the roof cladding with SDM Screw and rivets @ 1000 mm max
c/c between girts

RPFL Zed & Cee sections are roll formed from
GALVSTEEL, complying with AS1397-2001. Purlin
size as per structural drawings.
Supporting steel structure as per
requirements from engineers